

1

2

3

4

Note:

Materials:

.Plunger: Brass Au over 0.25um Ni.

.Spring: SUS

.Barrel: Brass Au over 0.25um Ni.

Mechanical:

.Contact force: 40g±10g at 1.0mm working stroke

.Full stroke: 1.40mm

.Life test: 50,000 cycles

Electrical:

.Rated voltage: DC12V, 1A Max.

.Contact resistance: 50 milliohm Max.

Standard tolerances are:

.Diameters: +/-0.05mm

.Lengths: +/-0.15mm

.Angles: +/-2°



Φ1.00

Φ1.50

Φ1.55

Φ1.80

Φ1.00

0.40


18.30

2.75

20.00±0.1

BOM

Part	NO.	Qty
Plunger	B263-B1010	1
Barrel	M501-P1010	1
Spring	B263-S1001	1

SCALE	20:1	UNIT:mm	THIS DOCUMENT IS THE SOLE PROPERTY OF CFE CORPORATION CO.,LTD., AND SHOULD NOT BE USED IN WHOLE OR IN PART WITHOUT PRIOR WRITTEN PERMISSION.		 东莞市川富电子有限公司 CFE CORPORATION CO.,LTD.	
ANGEL	±1°	A4	SHEET: 1 of 1			
0~6	±0.05				PART NO.	BP26311
6~30	±0.10	DRAW			FILE NAME	BP263XX
30~150	±0.15	CHECK			TITLE.	Barrel
GENERAL TOLERANCE UNLESS OTHERWISE NOTED		APPRO				

	D0	2014.09.02	NEW
ECN(DCN) NO.	REV	DATE	DESCRIPTION